(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



T GENERAL IN COLUMN CONTRACTOR DE LA COLUMN COLUMN

(43) International Publication Date 15 January 2004 (15.01.2004)

PCT

(10) International Publication Number WO 2004/005088 A1

(51) International Patent Classification⁷: G08B 21/22, 21/14

B60R 27/00,

(21) International Application Number:

PCT/GB2003/002892

(22) International Filing Date:

4 July 2003 (04.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0215611.5

5 July 2002 (05.07.2002) GB

0306033.2

17 March 2003 (17.03.2003) GB

(71) Applicant and

(72) Inventor: MARRIOTT, Paul [GB/GB]; 66 Jersey Close, Church Hill North, Redditch, Worcestershire B98 9LT (GB).

(74) Agent: FORRESTER KETLEY & CO; Chamberlain House, Paradise Place, Birmingham B3 3HP (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: INTRUSION DETECTOR



(57) Abstract: An intrusion detector for the vehicle, the detector being attachable to the vehicle, wherein the intrusion detector comprises a carbon dioxide detector responsive to the presence of carbon dioxide in a compartment of the vehicle, and wherein the intrusion detector is operable to generate an alarm if the proportion of carbon dioxide in the volume exceeds a selected level.

